



T25 Series Rotary Tillers

Heavy Duty Tillers from 80 to 100 Inches (70-90 HP)



The T25 Series Heavy Duty Gear Drive Tillers feature an easy change 4 speed gearbox allowing you to set your tiller speed to match field conditions. The load bearing frame on which the gearbox and super heavy duty protective hood are mounted make this machine extremely sturdy for even the most demanding applications. All Phoenix line tillers are specially designed to reduce the possibility of clogging even in wet or sticky soil conditions.

Standard Features Include:

- Series 8 PTO Clutch With 4 Plate Slip Clutch by Eurocardan
- 6 Heavy Duty Tines Per Flange
- 4 Speed Gearbox W/ Shift Lever
- Gear Drive Transmission in Oil Bath
- Double Torque Tube
- Adjustable Upper and Lower Hitch Points.



Specifications	T25-80GE	T25-92GE	T25-100GE
Working Width (in.)	81"	91"	100"
Working Depth (in.)	9"	9"	9"
Blades/Flange	6	6	6
Total Blades	48	54	60
Transmission	Gear Drive	Gear Drive	Gear Drive
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch
PTO Shaft Series	8	8	8
Horsepower Req. (HP)	70 - 100	70 - 100	70 - 100
Rotor Flange Diameter (in.)	6.3"	6.3"	6.3"
Rotor Flange Thickness (in.)	0.6"	0.6"	0.6"
Approximate Weight w/PTO (lbs)	1590 lbs	1722 lbs	1836 lbs
Rotor Speeds	4+2	4+2	4+2



For more information contact:
 Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Website: www.unifarmmachinery.com