

FARM-MAXX

FGCR-08 and FGCR-10 Carted Wheel Rakes



15" tires and heavy duty .27" teeth give you the ability to operate at high ground speeds with maximum raking efficiency and ease. A robust double acting hydraulic cylinder with heavy duty double ram design is standard for ease of operations with most tractor hydraulic systems. Each wheel features tapered roller bearings for long trouble free operation. The thick walled square tube frame is built to last for years under the most demanding applications.

Standard Features:

- Heavy Duty Square Tube Frame
- New 205/70-15 Tires
- Heavy Walled Round Tube Frames with Reinforcement Gussets
- Cast Steel Hubs with Tapered Roller Bearings
- .27" Thick Spring Steel Teeth
- Heavy Duty Individual Hydraulic Cylinders
- Hyd. Kicker Wheel Optional

Kicker Wheel



Model	FGCR-08	FGCR-10
Teeth Per Wheel	40	
Wheel Diameter	55"	
Teeth Diameter	.27"	
Windrow Adjustment	1.6' to 6.6'	
Working Width	17'-20'	17'-23'
Transport Width	9'10"	
Transport Length	15.7'	17.7'
HP	40	50
Kicker Wheel (Hydraulic)	Optional	Optional
Wt. Lbs.	1,322	1,455

* Unifarm reserves the right to change specifications without notice.



For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@unifarm.biz Website: www.unifarmmachinery.com