

FARM-MAX

FTL, FTM, and FTH Series Rotary Tillers Dependable Rugged Gear Drive Performance From 36 to 84 Inches



| Specifications | FTL-36G | FTL-48G | FTL-60G | FTM-65G | FTM-72G | FTH-84G |
|--------------------------|------------|------------|------------|------------|------------|---------------|
| Working Width(in.) | 36 | 48 | 60 | 65 | 72 | 84 |
| Working Depth(in.) | 7 | 7 | 7 | 8 | 8 | 8 |
| Blades/Flange | 6 | 6 | 6 | 6 | 6 | 6 |
| Total Flanges | 4 | 6 | 7 | 8 | 9 | 9 |
| Total Blades | 24 | 36 | 42 | 48 | 54 | 54 |
| Transmission | Gear | Gear | Gear | Gear | Gear | Gear |
| Hitch | ASAE Cat I | ASAE Cat I | ASAE Cat I | ASAE Cat I | ASAE Cat I | ASAE Cat I/II |
| Quick Hitch Compatible | Yes | Yes | Yes | Yes | Yes | Yes |
| PTO W/ SLIP CLUTCH | Yes | Yes | Yes | Yes | Yes | Yes |
| PTO SERIES | 4 | 4 | 4 | 4 | 4 | 5 |
| PTO Power Required (HP) | 15-25 | 25-35 | 25-40 | 30-55 | 30-55 | 35-70 |
| Optimum PTO Speed (RPM) | 540 | 540 | 540 | 540 | 540 | 540 |
| Rotor Speed (RPM) | 245 | 242 | 242 | 241 | 241 | 241 |
| OffSet L+R 4" | Yes | Yes | Yes | Yes | Yes | Yes |
| Rotor Swing Diameter(in) | 14.8 | 14.8 | 14.8 | 17.1 | 17.1 | 18.9 |
| Weight W/PTO LBS | 392 | 454 | 496 | 682 | 738 | 1062 |

- ASAE Quick Hitch Compatible Welded Hitch
- Boron Steel Tines for Long Life
- Heavy Duty Zinc Plated Jack Stand
- Heavy Drag Board with Zinc Plated Check Chains
- Adjustable Lower Hitch Blocks

* Unifarm reserves the right to change specifications without notice.



For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@unifarm.biz Website: www.unifarmmachinery.com