

FARM-MAXX

Farm-Maxx Three Point Rotary Cutters Models from 48 inches to 10 Feet!



Standard features include:

- Reinforced Fabricated deck
- Heavy duty pressed pan type stump jumper
- Laminated tailwheel with greasable bearing
- Heavy duty driveline W/Shear Bolt Std.
- Slip Clutch PTO Std. on Larger Models
- Floating Top Hitch
- Dual laminated tail wheel standard on Model URC-84
- Std Safety Chains on 84 - 120 Models

Model	Agri-X 4	Agri-X 5	Agri-X6	Agri-X 6SC	URC-84	URC-96	URC-120
Cutting Width	4ft	5 ft	6 ft	6ft	7 ft	8ft	10ft
Cutting Height	2-10 Inches				2 to 12 inches		
Hitch	Cat 1, 3 Point, Floating Top				Cat 1, 3 Point, Floating Top	Cat I, II Hitch	
Deck Thickness	11 Gauge				10 gauge		
Gearbox	40HP				80 HP		
PTO Drive Shaft	Series 4				Series 6		
Driveline Protection	1/2 Shear Bolt			Slip Clutch	Slip Clutch		
Tailwheel	Single Laminated				Double Laminated Wheels		
Tractor HP Range	15-30HP	25 - 35 HP	25 - 45 HP	25-45	50-80HP		
Machine Weight ^{*manuf's Est}	380	475	601	675	1,095	1,550	2,090

Note: Specifications and pricing subject to change without notice. Shipping weights are approximate and may vary subject to variations in packaging.



For more information, contact:

Uniform Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@uniform.biz Web Site: www.uniform.biz