

FARM-MAXX

Farm-Maxx FRG Series Root Grapple

54" - 60" - 66" - 72" ROOT GRAPPLES



Standard Features Include:

- AR400 Abrasion Resistant Steel
- Dual Cylinders on 60", 66", 72"
- Quick Attach Compatible
- 1/2" Male & Female Quick Connectors Included
- Tuff-Flex® Protective Hose Sleeve Standard

Model	FRG-54	FRG-60	FRG-66	FRG-72
Grapple Width	37.4" (949 mm)	47.6" (1210 mm)	51.7" (1314 mm)	57.8" (1467 mm)
Width	54" (1372 mm)	60" (1528 mm)	66" (1676.6 mm)	72" (1829 mm)
Overall Height	28.9" (733 mm)	28.9" (733 mm)	28.9" (733 mm)	28.9" (73 mm)
Grapple Opening	33" (813 mm)	33" (813 mm)	33" (813 mm)	33" (813 mm)
Teeth No.	6	8	8	9
Cylinder(s)	Single	Double	Double	Double
Weight	315lb	359lb	380lb	401lb

UNIFARM
MACHINERY CORPORATION

For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
Email: sales@unifarm.biz Website: www.unifarmmachinery.com

