



## T30 Series Rotary Tillers

### Heavy Duty Tillers from 90 to 120 Inches (90-160 HP)



T30 Series Gear Drive Rotary Tillers from Phoenix are extremely reliable and suited to even the most demanding applications and soil conditions. The super strong frame, heavy duty steel plate box-type bonnet, and four speed side drive in oil bath make these heavy duty machines dependable work horses on any job. From the oversized rotor tube with optional double flange to the double extended torque tubes, this machine is built to give you years of trouble free service.

Get the most out of your T30 Series Rotary Tiller with optional Roller Packer Kit, Hydraulic Roller Packer Control Kit, and Double Flanged Rotor Tube.

#### Standard Features Include:

- Series 8 PTO Clutch With 4 Plate Slip Clutch by Eurocardan
- 6 Heavy Duty Tines Per Flange
- 2+2 Gearbox
- Gear Drive Transmission in Oil Bath
- Double Torque Tube

#### Available Options on Request:

- Double Flanges
- Roller Packer Kit
- Hydraulic Roller Packer Control Kit
- Spiked Roller Packer Kit

SPECIFICATIONS	T30-90GE	T30-100GE	T30-112GE	T30-120GE
<b>Working Width (in.)</b>	<b>90</b>	<b>100</b>	<b>112</b>	<b>120</b>
<b>Working Depth (in.)</b>	<b>4-8</b>	<b>4-8</b>	<b>4-8</b>	<b>4-8</b>
<b>Blades/Flange</b>	<b>6</b>	<b>6</b>	<b>6</b>	<b>6</b>
<b>Total Blades</b>	<b>54</b>	<b>60</b>	<b>66</b>	<b>72</b>
<b>Transmission</b>	<b>Gear Drive</b>	<b>Gear Drive</b>	<b>Gear Drive</b>	<b>Gear Drive</b>
<b>Driveline Protection</b>	<b>Slip Clutch</b>	<b>Slip Clutch</b>	<b>Slip Clutch</b>	<b>Slip Clutch</b>
<b>PTO Shaft Series</b>	<b>8</b>	<b>8</b>	<b>8</b>	<b>8</b>
<b>PTO Requirement (HP)</b>	<b>90-160</b>	<b>90-160</b>	<b>90-160</b>	<b>90-160</b>
<b>Rotor Flange Diameter (in.)</b>	<b>6.3</b>	<b>6.3</b>	<b>6.3</b>	<b>6.3</b>
<b>Rotor Flange Thickness (in.)</b>	<b>0.6</b>	<b>0.6</b>	<b>0.6</b>	<b>0.6</b>
<b>Approximate Weight W/PTO (LBS)</b>	<b>2515</b>	<b>2725</b>	<b>2879</b>	<b>3108</b>
<b>Rotor Speeds</b>	<b>2+2</b>	<b>2+2</b>	<b>2+2</b>	<b>2+2</b>

\* Uniform reserves the right to change specifications without notice.



For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: [sales@unifarm.biz](mailto:sales@unifarm.biz) Website: [www.unifarmmachinery.com](http://www.unifarmmachinery.com)