



T5 Series Rotary Tillers

36 to 60 Inch Rotary Tillers so good you hate to get them dirty!



Phoenix T5 Series Rotary Tillers are well suited for hobby farmers, fruit and vegetable growers, landscapers nurseries, vineyards, and grounds maintenance operations. Applications include: soil conditioning and weed control, fertilizer incorporation, and seed bed preparation. Available in working widths from 36" to 60"

Standard Features Include:

- Six Tines Per Flange
- Adjustable/Off Settable Lower and Upper Hitch Blocks (for up to 4" of offset)
- Drive Housing Oil Level Site Glass for Ease of Maintenance
- Multi-position Heavy Duty Zinc Plated Jack Stand
- Powder Coat Paint Finish Available in Red Or Orange
- Heavy Duty Adjustable Drag Board With Zinc Plated Check Chain
- Series 4 PTO Shaft With Slip Clutch

Specifications	T5-36	T5-40	T5-44	T5-48	T5-52	T5-56	T5-60
Working Width (Inches)	36	40	44	48	52	56	60
Working Depth (Inches)	7	7	7	7	7	7	7
Blades per Flange	4	6	6	6	6	6	6
Total Blades	24	30	30	36	36	42	42
Side Drive	#80 Chain	#80 Chain	#80 Chain	#80 Chain	#80 Chain	#80 Chain	#80 Chain
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat I	Cat I	Cat I	Cat I	Cat I	Cat I	Cat I
PTO Shaft Series	4	4	4	4	4	4	4
PTO Power Required (HP)	15-20	15-20	15-20	20-35	20-35	20-35	20-35
Optimum PTO Speed (RPM)	540	540	540	540	540	540	540
Rotor Flange Diameter (Inches)	6.3	6.3	6.3	6.3	6.3	6.3	6.3
Rotor Flange Thickness (Inches)	0.4	0.4	0.4	0.4	0.4	0.4	0.4
Aproximate Weight (LBS)	300	330	348	363	396	430	441

* Uniform reserves the right to change specifications without notice.



For more information contact:
 Uniform Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Website: www.unifarmmachinery.com