



FLXM Heavy Duty Flex Wing Mowers The Next Step in Value and Performance!



FLXM Flex Wing Mowers from Phoenix offer you unsurpassed performance in mowing widths from 12 to 20 feet. Operating ground speeds of up to 10MPH together with superb cut quality mean less time in the field. Wide angle PTO shafts, advanced floating deck/frame linkages, and a combination of fixed and pivoting high flotation wheels give you superb maneuverability and ease of operation even in the most demanding field conditions. Ideally suited for parks, athletic fields, airports, sod farms, golf courses, or other large grassy areas where appearance and quality of cut are critical, these machines will save you time and money year after year.

Standard Features Include:

- Extra Heavy Duty Transport Frame W/Easy Adjust Telescoping Wings
- Double Pivot Floating Hinge Points at Each Deck for Maximum Float and Tracking
- Hydraulic Locking/Unlocking System with Double Acting Cylinders Standard
- Cool and Quiet Running Heavy Duty Gearboxes with Integral Oil Level Sight Glasses
- Series 6 Main PTO Shaft W/CV Joint by Eurocardan is Standard Equipment
- Wing Decks Feature Series 4 Eurocardan PTO Shafts as Standard Equipment
- One Step Spindle Greasing Without Removing Shields
- Four 13" High Flotation Tires Per Deck For Excellent Tracking and Minimum Compaction.
- "No Tools Required" Belt Shield Removal
- Standard Anti Scalping Rollers on Each Deck
- Adjustable Carrier Frame Height Allows for Matching with Multiple Tire and Drawbar Height Combinations.



Model	FLXM-312	FLXM-315	FLXM-317	FLXM-320
Working Width (Feet)	12	15	17	20
Rated Horsepower (Min)	35	40	45	55
Weight (LBS)	3,130	3,264	3,352	4,366
Deck Configuration	48-48-60	60-60-72	72-72-72	84-84-84
Anti-Scalp Roller	Standard	Standard	Standard	Standard
Tire Size	13 x 5.00-6	13 x 5.00-6	13 x 5.00-6	13 x 5.00-6
Cutting Height (Inches)	1" - 5"	1" - 5"	1" - 5"	1" - 5"
PTO (Main)	#6CV	#6CV	#6CV	#6CV
PTO (Wing)	#4	#4	#4	#4
Ground Pressure (Lb/Sq. In)	7.10	7.30	7.70	9.90
Blade Tip Speed (Ft/Min)	13,808	14,113	14,198	15,274
Transport Width	7' 3"	7' 8"	8' 3"	9' 8"
Maximum Width	12' 2"	15' 1"	17' 1"	20'
Maximum Length	14'	15'	15' 9"	16' 5"

* Uniform reserves the right to change specifications without notice.



For more information contact:
 Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Website: www.unifarmmachinery.com